

HOFMANN 505 Balancing Compound

- Quick and easy balancing No balancer required, simply tear open the bag and toss it into the assembly.
- Increased fuel efficiency A smoother ride and reduced rolling resistance mean longer tire life, better tread and contact to road, making every mile more efficient.
- Prolonged tire life
 Longer lasting tire tread and even tire
 wear due to fewer vibrations keeps
 your tires running smoother and
 cooler, ultimately lasting longer.

• TPMS safe Specially coated compound has no

adverse effects on TPMS sensors or inner tire liners. A special valve core and a high-quality metal valve cap are included in every bag to help protect your value.


- More driving comfort Vibration dampening increases comfort, thus causing less exhaustion for the driver.
- Environmentally friendly Lead-free.



HOW IT WORKS:

In a running tire, the balancing compound is dispersed along the tire walls due to the centrifugal force. As the compound can flow freely in the tire, it will constantly adjust to shifts in forces caused by changed imbalances, speeds and road conditions, delivering a smooth ride.





THE INTELLIGENT BALANCING COMPOUND:

The secret of the innovative Hofmann Power Weight Fusion Technology is the different size materials used in the balancing compound itself. The larger red kernels concentrate in the center of the tire and dampen the static imbalance. The smaller blue kernels shift more to the outer edges of the concentration and compensate wobbling which is caused by dynamic imbalance. The result is a smooth ride for the complete tire life.



See back for application chart

To Order 800-998-9897 myerstiresupply.com

HOFMANN 505 Balancing Compound Application Chart

For medium and heavy-duty truck tires

Myers #	Size	Weight	Master E	Box / Case			Contractor		
62958	XS	4 oz/120 g	16	bags					
62959	S	6 oz/180 g		bags	<u>315 / 7</u>	U R 22			
62960	М	8 oz/230 g		bags	Α	В	XL	LM	S XS
62961	L	10 oz/290 g		ags			Sarris Statement	With With	With With the
62962	XL	12 oz/350 g	0 8	ags					
Α		B HPV	V 505	Α	В	HPW 505	A	В	HPW 505
31/10.5		15 >	KS	265/7) 18	XS	285/60	22.5	L
225/75		16	KS	275/7) 18	S	295/60	22.5	L
245/75		16	KS	385/5	5 19.5	XL	305/60	22.5	L
265/75		16	KS	255/6) 19.5	S	315/60	22.5	L
285/75		16	S	385/6	5 19.5	XL	500/60	22.5	XL + XL
215/85		16	KS	225/7) 19.5	М	385/65	22.5	XL + XS
235/85		16	KS	245/7) 19.5	S	425/65	22.5	XL + S
245/70		17)	KS	265/7) 19.5	S	445/65	22.5	XL + S
265/70		17)	KS	275/7) 19.5	М	255/70	22.5	М
285/70		17	S	285/7) 19.5	М	265/70	22.5	М
245/75		17)	KS	295/7) 19.5	М	275/70	22.5	L
235/80		17 >	KS	305/7) 19.5	L	305/70	22.5	L
215/70	-	17.5)	KS	315/7) 19.5	L	315/70	22.5	L
235/70	-	17.5)	KS	275/6	5 20	S	295/75	22.5	XL
245/70	-	17.5)	KS	405/7) 20	XL + XS	315/75	22.5	XL
265/70		17.5	S	375/7	5 20	XL + XS	345/75	22.5	XL
315/70	-	17.5	М	425/7	5 20	XL + S	350/75	22.5	L + XS
205/75	-	17.5	KS	275/8) 20	L	445/75	22.5	L+L
215/75	-	17.5)	KS	335/8) 20	XL	255/80	22.5	М
225/75	-	17.5)	KS	475/8) 20	XL + XL	275/80	22.5	L
235/75	-	17.5	S	365/8	5 20	XL + XS	295/80	22.5	XL
245/75	-	17.5	S	395/8	5 20	XL + S	315/80	22.5	XL
205/80	-	17.5	S	10.5	20	L	11	22.5	L
225/80	-	17.5	S	12.5	20	XL	12	22.5	XL
315/80	-	17.5	L	14.5	20	XL + XS	13	22.5	XL
225/90	-	17.5	S	24	20.5	L	405/70	24	L+L
8	-	17.5)	KS	495/4	5 22.5	XL + S	445/70	24	XL + L
8.5	-	17.5	KS	355/5) 22.5	XL	455/70	24	XL + XL
9	-	17.5	S	435/5) 22.5	XL + XS	495/70	24	XL + XL
9.5	-	17.5	S	445/5) 22.5	XL + XS	285/75	24.5	XL
10	-		М	455/5) 22.5	XL + XS	11	24.5	XL
275/65			S	385/5	5 22.5	XL		To Order	_

800-998-9897 myerstiresupply.com